

12-30-99

A

DOCKET NO. : BELL-0017/99230

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of:

EL219292629US

Greg Griffith, Charles M. Link, II

Serial No.: Not Yet Assigned

Group Art Unit: Not Yet Assigned

Filing Date: Herewith

Examiner: Not Yet Assigned

For: METHOD OF COUPLING PORTABLE COMMUNICATIONS DEVICE TO
FIRST NETWORK BY WAY OF SECOND NETWORK

EXPRESS MAIL LABEL NO: EL219292629US
DATE OF DEPOSIT: December 29, 1999

Box ☒ Patent Application
☐ Provisional ☐ Design

Assistant Commissioner for Patents
Washington DC 20231

Sir:

PATENT APPLICATION TRANSMITTAL LETTER

Transmitted herewith for filing, please find

☒ A Utility Patent Application under 37 C.F.R. 1.53(b).


It is a continuing application, as follows:

☐ continuation ☐ divisional ☐ continuation-in-part of prior application number
____/____.

☐ A Provisional Patent Application under 37 C.F.R. 1.53(c).

☐ A Design Patent Application (submitted in duplicate).

Including the following:



09473604 12/29/99

☐ Provisional Application Cover Sheet.

☒ New or Revised Specification, including pages 1 to 15 containing:

☒ Specification

☒ Claims

☒ Abstract

☐ Substitute Specification, including Claims and Abstract.

☐ The present application is a continuation application of Application No. _____ filed _____. The present application includes the Specification of the parent application which has been revised in accordance with the amendments filed in the parent application. Since none of those amendments incorporate new matter into the parent application, the present revised Specification also does not include new matter.

☐ The present application is a continuation application of Application No. _____ filed _____, which in turn is a continuation-in-part of Application No. _____ filed _____. The present application includes the Specification of the parent application which has been revised in accordance with the amendments filed in the parent application. Although the amendments in the parent C-I-P application may have incorporated new matter, since those are the only revisions included in the present application, the present application includes no new matter in relation to the parent application.

☐ A copy of earlier application Serial No. _____ Filed _____, including Specification, Claims and Abstract (pages 1 - @@), to which no new matter has been added TOGETHER WITH a copy of the executed oath or declaration for such earlier application and all drawings and appendices. Such earlier application is hereby incorporated into the present application by reference.

☐ Please enter the following amendment to the Specification under the Cross-Reference to Related Applications section (or create such a section) : "This Application:

☐ is a continuation of ☐ is a divisional of ☐ claims benefit of U.S. provisional Application Serial No. _____ filed _____

- ☐ Signed Statement attached deleting inventor(s) named in the prior application.
- ☐ A Preliminary Amendment.
- ☒ Three Sheets of ☒ Formal ☐ Informal Drawings.
- ☐ Petition to Accept Photographic Drawings.
- ☐ Petition Fee
- ☒ An ☐ Executed ☒ Unexecuted Declaration or Oath and Power of Attorney.
- ☐ An Associate Power of Attorney.
- ☐ An ☐ Executed ☐ Copy of Executed Assignment of the Invention to _____
- ☐ A Recordation Form Cover Sheet.
- ☐ Recordation Fee - \$40.00.
- ☐ The prior application is assigned of record to _____
- ☐ Priority is claimed under 35 U.S.C. § 119 of Patent Application No. _____
filed _____ in _____ (country).
- ☐ A Certified Copy of each of the above applications for which priority is claimed:
- ☐ is enclosed.
- ☐ has been filed in prior application Serial No. _____ filed _____.
- ☐ An ☐ Executed or ☐ Copy of Executed Earlier Statement Claiming Small Entity Status under 37 C.F.R. 1.9 and 1.27
- ☐ is enclosed.
- ☐ has been filed in prior application Serial No. _____ filed _____
said status is still proper and desired in present case.

Bell-0017-4035-460

- ☐ Diskette Containing DNA/Amino Acid Sequence Information.
- ☐ Statement to Support Submission of DNA/Amino Acid Sequence Information.
- ☐ The computer readable form in this application _____, is identical with that filed in Application Serial Number _____, filed _____. In accordance with 37 CFR 1.821(e), please use the ☐ first-filed, ☐ last-filed or ☐ only computer readable form filed in that application as the computer readable form for the instant application. It is understood that the Patent and Trademark Office will make the necessary change in application number and filing date for the computer readable form that will be used for the instant application. A paper copy of the Sequence Listing is ☐ included in the originally-filed specification of the instant application, ☐ included in a separately filed preliminary amendment for incorporation into the specification.
- ☐ Information Disclosure Statement.
- ☐ Attached Form 1449.
- ☐ Copies of each of the references listed on the attached Form PTO-1449 are enclosed herewith.
- ☐ A copy of Petition for Extension of Time as filed in the prior case.
- ☐ Appended Material as follows: _____
- ☒ Return Receipt Postcard (should be specifically itemized).
- ☐ Other as follows: _____

FEE CALCULATION:

- ☐ Cancel in this application original claims _____ of the prior application before calculating the filing fee. (At least one original independent claim must be retained for filing purposes.)

			SMALL ENTITY		NOT SMALL ENTITY	
			RATE	FEE	RATE	FEE
PROVISIONAL APPLICATION			\$75.00	\$	\$150.00	\$
DESIGN APPLICATION			\$155.00	\$	\$310.00	\$
UTILITY APPLICATIONS BASE FEE			\$380.00	\$	\$690.00	\$690.00
UTILITY APPLICATION; ALL CLAIMS CALCULATED AFTER ENTRY OF ALL AMENDMENTS						
	No. Filed	No. Extra				
TOTAL CLAIMS	11- 20 =	0	\$9 each	\$	\$18 each	\$0
INDEP. CLAIMS	1- 3 =	0	\$39 each	\$	\$78 each	\$0
FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM			\$130	\$	\$260	\$0
ADDITIONAL FILING FEE				\$		\$0
TOTAL FILING FEE DUE				\$		\$690.00

- ☒ A Check is enclosed in the amount of \$ 690.00.
- ☒ The Commissioner is authorized to charge payment of the following fees and to refund any overpayment associated with this communication or during the pendency of this application to deposit account 23-3050. This sheet is provided in duplicate.
- ☐ The foregoing amount due.
- ☒ Any additional filing fees required, including fees for the presentation of extra claims under 37 C.F.R. 1.16.
- ☒ Any additional patent application processing fees under 37 C.F.R. 1.17 or 1.20(d).
- ☐ The issue fee set in 37 C.F.R. 1.18 at the mailing of the Notice of Allowance.
- ☒ The Commissioner is hereby requested to grant an extension of time for the appropriate length of time, should one be necessary, in connection with this filing or any future filing submitted to the U.S. Patent and Trademark Office in the above-


6652221 4096460

identified application during the pendency of this application. The Commissioner is further authorized to charge any fees related to any such extension of time to deposit account 23-3050. This sheet is provided in duplicate.

SHOULD ANY DEFICIENCIES APPEAR with respect to this application, including deficiencies in payment of fees, missing parts of the application or otherwise, the United States Patent and Trademark Office is respectfully requested to promptly notify the undersigned.

Date:

Dec. 29 1999



Steven H. Meyer

Registration No. 37,189

Woodcock Washburn Kurtz
Mackiewicz & Norris LLP
One Liberty Place - 46th Floor
Philadelphia PA 19103
Telephone: (215) 568-3100
Facsimile: (215) 568-3439

© 1997 WWKMN

054704 4092450

USPS EXPRESS MAIL MAILING LABEL NO. EL219292629US

Title of the Invention

METHOD OF COUPLING PORTABLE COMMUNICATIONS DEVICE TO FIRST
NETWORK BY WAY OF SECOND NETWORK

Field of the Invention

5 The present invention relates to a method and apparatus for extending coverage for a portable communications device such as an interactive (two-way) communications device. In particular, the present invention relates to extending coverage for a two-way pager in areas where the pager cannot transmit to a receiving station and/or receive from a transmitting station.

10 **Cross-Reference to Related Applications**

 The present application is related to and filed concurrently with U.S. Patent Application No. 09/____,____, Attorney Docket No. Bell-0015 / 99228, entitled "PORTABLE COMMUNICATIONS DEVICE COUPLABLE TO FIRST NETWORK BY WAY OF SECOND NETWORK"; U.S. Patent Application No. 09/____,____, Attorney
15 Docket No. Bell-0016 / 99229, entitled "EMULATING BASE STATION FOR COUPLING PORTABLE COMMUNICATIONS DEVICE TO FIRST NETWORK BY WAY OF SECOND NETWORK"; and U.S. Patent Application No. 09/____,____, Attorney Docket No. Bell-0008 / 99157, entitled "CRADLE FOR ACCEPTING PORTABLE COMMUNICATIONS DEVICE AND COUPLING PORTABLE COMMUNICATIONS
20 DEVICE TO FIRST NETWORK BY WAY OF SECOND NETWORK", each of which is

hereby incorporated by reference.

Background of the Invention

Interactive two-way pagers and a pager network system in support thereof are known. Examples of such two-way pagers include the RESEARCH IN MOTION (RIM) "BLACKBERRY" two-way pager designed and/or marketed by RESEARCH IN MOTION Limited of Waterloo, Ontario, Canada and the MOTOROLA two-way pager designed and/or marketed by MOTOROLA Corporation of Schaumburg, Illinois, USA. Such pagers typically include a battery compartment for receiving a battery, a processor, memory, a data screen for displaying alpha-numeric data, a micro-size keyboard for entering alpha-numeric data, a radio receiver for receiving data over air, and a radio transmitter for transmitting data over air. Accordingly, data may be transmitted from one pager and received by another by way of the network system. Likewise, data from a source external to the network system may be received by a pager, and such pager may transmit data to a destination external to the network system. In addition, such pagers typically include a serial port or the like by which data may be uploaded and/or downloaded, for example during pager initialization, set-up, and upgrade at a pager sales and/or service center.

Examples of pager network systems include the MOBITECH network designed and/or marketed by ERICSSON MOBILE COMMUNICATIONS AB of Sweden and the REFLEX network designed and/or marketed by MOTOROLA Corporation of Schaumburg, Illinois, USA. Such network systems ("networks") typically include one or more base stations, where each base station has associated with it a plurality of geographically spaced base transmitters, each of which can potentially transmit the data received by the radio receiver of the pager, and a plurality of geographically spaced base receivers, each of which can potentially receive the data transmitted by the radio transmitter of the pager. The base transmitters and the base receivers are spread out over a network coverage area, and each is assigned particular transmitting or receiving frequencies by its respective base station.

As should be appreciated, each base station is responsible for directing pager data to its ultimate destination or from its ultimate source. Such base station also

assigns the frequencies to the base transmitters and base receivers, keeps track of the locations of pagers with respect to base transmitters and base receivers, assigns each pager to a particular base transmitter and to a particular base receiver as the pager is moved through the network coverage area, or at least through the portion thereof that the base station is responsible for, and transmits information to each pager regarding the assigned base transmitter and assigned base receiver and/or frequencies thereof, among other things. Since the pager must acknowledge receipt for data verification purposes and the like, among other things, the pager must always be in two-way communication with the network, even if only receiving data from such network.

Typically, the base transmitters operate at a relatively high power, owing to the fact that each pager is battery-operated and the receiver therein operates at a relatively low power. Also owing to the fact that each pager is battery-powered and the transmitter therein likewise operates at a relatively low power, the base receivers are typically concentrated at a higher number per geographical area than the transmitter base stations in the network coverage area. Accordingly, it is statistically more likely that a pager is closer to a base receiver than to a base transmitter. Correspondingly, it is also more likely that a pager in a fringe (i.e., area on the edge) or marginal (i.e., an area with poor transmission quality) portion of the network coverage area can receive data from a base transmitter, but that a base receiver cannot receive data from such pager, owing to the relatively low transmitting power of such pager.

The network coverage area for a pager network is typically finite. For example, such network coverage area may roughly correspond to a state or region, a portion of a state or region, a metropolitan area, a metropolitan area extending over portions of several states or regions, or the like. Accordingly, through cooperative service agreements between networks, 'roaming' pager coverage may be provided for a pager outside the network coverage area of its 'home' network. With such cooperative service agreements, the over-all pager coverage area encompasses a large portion of urban areas in the United States, and many rural areas too. Inevitably, though, there are significant portions of the United States where pager coverage is not available. As should be appreciated, coverage for a pager is not available anywhere the pager cannot communicate with both a base receiver and a base transmitter to achieve the aforementioned two-way

communications link. For example, coverage is not available in fringe or marginal portions of the network coverage area or the over-all pager coverage areas (if roaming coverage is provided), as was pointed out above, and in areas external to the network coverage area or the over-all pager coverage areas (if roaming coverage is provided). This is true even if the pager can communicate with a base transmitter. Of course, coverage will also not be available anywhere the pager cannot communicate with a base transmitter, but for the reasons specified above, it is more likely that loss of communication with any base receiver will occur first, or at least concurrently.

Equally inevitably, individuals with two-way pagers or the like visit areas where coverage is not available, both in and out of the United States, and such individuals would like some sort of continued two-way paging service even though in such areas without coverage. Accordingly, a need exists for a method and apparatus to provide coverage for a two-way pager or the like, especially when the pager is outside the aforementioned coverage area.

15

Summary of the Invention

In the present invention, a cradle accepts a portable communications device (PCD) such as a pager, where the PCD is normally in radio communication with a first network. The cradle couples the accepted PCD to the first network by way of a second network when the PCD is out of radio communication with the first network. The PCD includes an externally accessible port from which communications data is accessible, and the cradle is sized to accept the PCD and includes a port connector for coupling with the externally accessible port of the accepted PCD, a network connector for coupling the cradle and by extension the PCD to the second network, and a network communications device for interfacing between the port connector and the network connector. In a variation, the cradle is dispensed with and the PCD includes the network connector and network communications device.

To couple the PCD to the first network by way of the second network, the PCD is coupled to the second network, and is caused to leave a first network mode and enter a second network mode. The PCD then establishes a network connection with the first network by way of the second network, and enters into communication with the first

network by way of the second network.

An emulating base station couples the PCD to the first network by way of the second network and includes a network connection for interfacing with the first network, a network communications device for interfacing with the second network, and a
5 server coupled to the first network by the network connection and coupled to the second network by way of the network communications device. The server is programmed to emulate a radio base station.

Brief Description of the Drawings

The foregoing summary, as well as the following detailed description of
10 preferred embodiments of the present invention, will be better understood when read in conjunction with the appended drawings. For the purpose of illustrating the invention, there are shown in the drawings embodiments which are presently preferred. As should be understood, however, the invention is not limited to the precise arrangements and instrumentalities shown. In the drawings:

15 Fig. 1 is a block diagram showing a two-way pager or the like and a base station in accordance with one embodiment of the present invention;

Fig. 2 is a block diagram showing the two-way pager or the like and the base station of Fig. 1 in accordance with another embodiment of the present invention; and

20 Fig. 3 is a flow chart depicting steps employed with the two-way pager and the base station of Figs. 1 and 2 in accordance with one embodiment of the present invention.

Detailed Description of Preferred Embodiments

Certain terminology may be used in the following description for convenience only and is not considered to be limiting. The words "left", "right", "upper",
25 and "lower" designate directions in the drawings to which reference is made. The words "inwardly" and "outwardly" are further directions toward and away from, respectively, the geometric center of the referenced object. The words "vertical" and "horizontal" in the present application designate orientations with respect to an object when such object is positioned in a particular and/or customary manner, but do not restrict the present

invention to the object in such position. The terminology includes the words above specifically mentioned, derivatives thereof, and words of similar import.

Referring now to Fig. 1, a pager 10 or the like and a base station 12 or the like are shown in accordance with one embodiment of the present invention. As was discussed above, and as shown, a typical two-way pager 10 is intended to be in communication with a pager network 13 and may include a battery compartment for receiving a battery 14, a processor 16, memory 18, an output device such as a data screen 20 for displaying alpha-numeric data, an input device such as a micro-size keyboard 22 for entering alpha-numeric data, a radio receiver 24 for receiving data over air, and a radio transmitter 26 for transmitting data over air. Notably, any particular two-way pager 10 may be employed without departing from the spirit and scope of the present invention, and such pager 10 need not necessarily include all of the aforementioned elements 14-26, again without departing from the spirit and scope of the present invention. For example, such pager 10 need not necessarily have the keyboard 22 or the data screen 20, and could instead or in addition have a speaker and/or a microphone, a video and/or still camera and/or a video screen, and/or the like.

Importantly for purposes of the present invention, the pager 10 also includes an externally accessible serial port 28 or the like by which data may be uploaded and/or downloaded. As was discussed above, such serial port 28 has heretofore been employed for services such as pager initialization, set-up, and upgrade at a pager sales and/or service center. Nevertheless, the pager 10 is capable of interacting with a device in the field by way of such serial port 28.

In one embodiment of the present invention, and as seen in Fig. 1, when the pager 10 is in an area where coverage is not available, such pager 10 may be placed in a cradle 30 or the like and thereby establish contact with the base station 12 by way of a network 32 such as a public switched (i.e., land line) telephone network, a mobile switching (i.e., mobile or cellular) network, an external computing network such as the Internet, an internal computing network, and the like. The public switched telephone network or the mobile switching network are most likely preferred due to their availability even in many remote and even wilderness locations. Such public switched telephone network or the mobile switching network may also be employed to dial into the

aforementioned internal or external computing networks.

Preferably, the cradle 30 includes a serial port connector 34 for coupling with the serial port 28 of the pager 10. As may be appreciated, the cradle 30 and the pager 10 may be constructed such that a positive connection between the serial port connector 34 and the serial port 28 is achieved merely by inserting such pager 10 into such cradle 30. For example, the cradle 30 and the pager 10 may include keying features for guiding and aligning such pager 10 and such cradle 30 during coupling to achieve such positive connection. Such keying features (not shown) may include but are not limited to complementary grooves and ridges, protrusions and recesses, and the like.

Also preferably, the cradle 30 includes a network connector 36 or the like for coupling the cradle 30 and by extension the pager 10 to the network 32. Of course, depending on the network 32, the network connector 36 will vary. For example, for the public switched telephone network, the network connector 36 is merely a telephone connector that receives a connector on one end of a telephone cord, where the other end is appropriately coupled to such network. For the mobile switching network, the network connector 36 may be a port that couples via an appropriate cable to a corresponding port on a mobile phone which in turn is registered on such network. Alternatively, the functional components of such mobile phone are integrated within such network connector 36. Other appropriate network connectors 36 may be employed based on the network 32 employed without departing from the spirit and scope of the present invention.

The cradle 30 further preferably includes a network communications device 38 for interfacing between the serial port connector 34 and the network connector 36. Of course, depending on the network 32, the network communications device 38 will vary. For example, for the public switched telephone network and the mobile switching network, the device 38 is an appropriately configured modem of a type that is typically employed for such purpose. For the internal or external computing network, the device 38 is an appropriately configured network interface such as a network interface card. Other appropriate network communications devices 38 may be employed based on the network 32 employed without departing from the spirit and scope of the present invention. In any instance, the device 38 receives data from the pager 10 by way of the serial port 28 thereof and sends such data to the network 32, and also receives data from the network 32 and

sends such data to the pager 10 by way of the serial port 28 thereof.

The cradle 30 may have its own power source, such as a battery or an AC power converter, and/or may derive its power from the received pager 10. Of course, if power use is more than minimal, it may be preferable that the cradle 30 have its own
5 power source so as not to excessively draw down the battery of such pager 10. If the cradle 30 has its own power source, such cradle 30 may supply additional power to the pager 10 so as to conserve the battery of such pager 10 and/or provide a power boost to the pager 10.

The base station 12 is a traditional base station in the sense that it performs
10 all the normal base station functions with regard to directing data to and from the pager 10. However, in one embodiment of the present invention, such base station 12 is a non-traditional base station in that it does not have any associated base transmitters or base receivers, and therefore need not concern itself with frequency assignment, pager tracking, pager assignment, and the like. Instead, such base station 12 is a dedicated base station
15 solely for servicing pagers 10 through the network 32. Accordingly, the base station 12 is coupled to and is a portal between the network 32 and the pager network 13 or the like. In such an instance, the base station 12 may include a server 40 coupled to the network 32 and to the pager network 13 and programmed to emulate all necessary two-way base station functions. Of course, to couple to the network 32, the base station 12 may also
20 have a network communications device 38 similar to the network communications device 38 in the cradle 30 (e.g., a modem). Moreover, to couple to multiple cradled pagers 10 by way of the network 32, multiple network communications devices 38 may be employed if necessary. To couple to the pager network 13, an appropriate network connection 42 may be employed. The details of the couplings, the connections, and the emulation are
25 generally known and therefore need not be described herein in further detail. Of course, the base station 12 may in fact be a non-dedicated base station that directs data from both the network 32 and traditional base transmitters and base receivers without departing from the spirit and scope of the present invention.

In operation, and referring now to Fig. 3, when two-way operation of the
30 pager 10 is disrupted because such pager 10 is out of range or is otherwise unable to contact its pager network 13, the user thereof appropriately places such pager 10 into the

cradle 30 (step 301) so that the serial port 28 of the pager 10 is coupled with the serial port connector 34 of the cradle 30. In addition, such user appropriately couples the cradle 30 to the network 32 by way of the network connector 36 (step 303) and whatever appropriate coupling is necessary (a telephone cable, for example, in the case of a public switched
5 telephone network).

Preferably, the pager 10 and the processor 16 therein are programmed to sense the connection to the cradle 30, and thereby enter a 'cradled' mode (step 305) where the radio transmitter 26 and radio receiver 24 therein are not employed. Instead, in such 'cradled' mode, the pager 10 and the processor 16 therein preferably gain the attention of
10 and establish control over the network communications device 38 (e.g., the modem) (step 307) within the cradle. Alternatively, the user may desire or be required to positively command the pager 10 to enter the cradled mode. Thereafter, the pager 10 and the processor 16 therein employ the network communications device 38 to establish a network connection with the base station 12 by way of the network 32 (step 309), and then the
15 pager 10 and processor 16 therein enter into two-way communication with the base station 12 by way of the network 32 (step 311) to send and receive pager information.

Preferably, during the time when two-way operation of the pager 10 is disrupted because such pager 10 is out of range or is otherwise unable to contact its pager network 13, and before the pager 10 enters into two-way communication with the base
20 station 12, any outgoing data from the pager 10 (such as outgoing messages and other outgoing information) is held in the memory 18 of the pager, and any incoming data destined for the pager 10 (such as incoming messages and other incoming information) is held in an appropriate memory location of the pager network 13. Accordingly, upon establishing two-way communication between the pager 10 and the base station 12 by way
25 of the network 32, such incoming and outgoing data is released and exchanged therebetween. Moreover, upon establishing two-way communication between the pager 10 and the pager network 13 by way of the base station 12 and the network 32, additional incoming and outgoing data (such as new messages and other information) may be composed and exchanged therebetween.

30 When the user wishes to end the session, such user may command the pager 10 to do so (step 313). The pager may also automatically end the session after a pre-

determined period of in-activity, among other things. The user can then remove the pager 10 from the cradle 30 (step 315) and de-couple the cradle 30 from the network 32 by way of the network connector 36 (step 317). Preferably, upon sensing removal from the cradle 30, the pager 10 returns to a 'normal' mode. Alternatively, the user positively commands
5 the pager 10 to return to normal mode. In one embodiment of the present invention, the user can leave the pager 10 in the cradle 30 and allow the pager 10 to automatically make a connection to the base station 12 by way of the network 32 on a periodic or predetermined basis.

Even if coverage is available for the pager 10 in the normal mode by way of
10 the pager network 13, such pager 10 may still be placed in cradled mode to establish two-way communication between the pager 10 and the base station 12 by way of the network 32 without departing from the spirit and scope of the present invention. Reasons for doing so may include anticipation of more reliable two-way communication, and availability of higher data transmission speeds, among other things, as well as user choice or preference.

15 In a variation on the embodiment of the present invention shown in Fig. 1, the actual structure of the cradle 30 is dispensed with, and the pager 10 or the like is coupled directly to the network communications device 38. Such direct coupling may for example be achieved by way of a serial port connector 34 at the end of a cable which is appropriately attached to such network communications device 38.

20 In another embodiment of the present invention, and referring now to Fig. 2, the cradle 30 of Fig. 1 is omitted, but the necessary contents and/or functionality therein are re-located to the pager 10', as is shown. Thus, the serial port connector 34 of Fig. 1 is no longer necessary, as the network communications device 38 and the connection between such network communications device 38 and the serial port 28 of the pager 10' are
25 internal to such pager 10'. The network communications device 38 (e.g., a modem) may thus comprise a chip set within the pager 10', or the processor 16 of the pager 10' may be programmed with the functionality of such device 38. The network connector 36 is still necessary but is now mounted directly to the pager 10' by appropriate means. Preferably, the network connector 36 is a micro-size connector to conserve space, and may for
30 example be of a type that 'flips out' from the pager 10' in a known manner.

In operation, the non-cradled pager 10' of Fig. 2 by definition cannot

automatically sense a connection to any cradle 30. Accordingly, such pager 10' must be positively commanded to enter 'cradled' mode, or must automatically sense a connection to the network connector 36 to enter 'cradled' mode. Likewise, such pager 10' must be positively commanded to enter 'normal' mode, or must automatically sense a

- 5 disconnection from the network connector 36 to enter 'normal' mode. Otherwise, the steps shown in Fig. 3 are performed in substantially the same manner.

Of course, the present invention also encompasses the use of two-way networked data communications devices and portable communications devices other than the pager 10. Similarly, the present invention encompasses the use of one-way pagers 10
10 and other similar devices. Likewise, the data from and to the pager 10 or the like may be directed by devices other than a base station 12, emulated or otherwise.

The programming necessary to effectuate the present invention, such as the programming run by the processor 16 of the pager 10 and the programming run by the server 40 of the base station, is known or is readily apparent to the relevant public.

- 15 Accordingly, further details as to the specifics of such programming is not believed to be necessary herein.

As should now be understood, in the present invention, a method and apparatus are provided to support coverage for a two-way pager or the like, especially when the pager is outside the coverage area of its pager network. Changes could be made
20 to the embodiments described above without departing from the broad inventive concepts thereof. It is understood, therefore, that this invention is not limited to the particular embodiments disclosed, but it is intended to cover modifications within the spirit and scope of the present invention as defined by the appended claims.

CLAIMS

1. A method of coupling a portable communications device (PCD) to a first network by way of a second network, the PCD normally in radio communication with the first network, the PCD being coupled to the first network by way of the second network when the PCD is out of radio communication with the first network, the method comprising:

coupling the PCD to the second network;
causing the PCD to leave a first network mode and enter a second network mode;
10 establishing a network connection with the first network by way of the second network; and
entering into communication with the first network by way of the second network.

2. The method of claim 1 for coupling a pager to a first network by way of a second network, the pager normally in radio communication with the first network, the pager being coupled to the first network by way of the second network when the pager is out of radio communication with the first network, the method comprising:

coupling the pager to the second network;
causing the pager to leave a first network mode and enter a second network mode;
20 establishing a network connection with the first network by way of the second network; and
entering into communication with the first network by way of the second network.

25 3. The method of claim 2 wherein the pager is a two-way pager, and

wherein entering into communication comprises entering into two-way communication with the first network by way of the second network.

4. The method of claim 1 further comprising:
de-coupling the PCD from the second network upon ending
5 communication therewith; and
causing the PCD to leave the second network mode and enter the
first network mode.
5. The method of claim 4 wherein the PCD has a serial port, wherein
coupling the PCD to the second network comprises:
10 placing the PCD into a cradle having a serial port connector and a
network connector so that the serial port of the pager is coupled with the serial port
connector of the cradle; and
coupling the network connector of the cradle to the second network,
and wherein de-coupling the PCD from the second network comprises removing the PCD
15 from the cradle.
6. The method of claim 1 wherein the PCD has a serial port, and
wherein coupling the PCD to the second network comprises:
placing the PCD into a cradle having a serial port connector and a
network connector so that the serial port of the pager is coupled with the serial port
20 connector of the cradle; and
coupling the network connector of the cradle to the second network.
7. The method of claim 1 wherein causing the PCD to enter the second
network mode comprises causing the PCD to gain the attention of and establish control
over a network communications device.
8. The method of claim 7 wherein causing the PCD to enter the second
25 network mode comprises causing the PCD to gain the attention of and establish control

over a modem.

9. The method of claim 7 wherein causing the PCD to enter the second network mode comprises causing the PCD to gain the attention of and establish control over a network interface card.
- 5 10. The method of claim 1 wherein establishing the network connection comprises establishing a network connection with a base station of the first network by way of the second network.
11. The method of claim 1 wherein entering into communication comprises entering into two-way communication with the first network by way of the
10 second network to send and receive information.

Abstract of the Disclosure

A method of coupling a portable communications device (PCD) to a first network by way of a second network is disclosed. The PCD is normally in radio communication with the first network, and is coupled to the first network by way of the second network when the PCD is out of radio communication with the first network. In particular, the PCD is coupled to the second network, and is caused to leave a first network mode and enter a second network mode. A network connection is established with the first network by way of the second network, and communication with the first network is entered into by way of the second network.

10 M:\BellSouth\Apps\Bell0017 (Extending Coverage -- Method)\Bell-0017 application in final wpd

FIG. 1





FIG. 2






FIG. 3

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In Re Application of:

EL219292629US

Greg Griffith, Charles M. Link, II

Group Art Unit: Not Yet
AssignedFor: METHOD OF COUPLING PORTABLE
COMMUNICATIONS DEVICE TO
FIRST NETWORK BY WAY OF
SECOND NETWORK

Examiner: Not Yet Assigned

DECLARATION AND POWER OF ATTORNEY

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name; and

I believe that I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a

☒ Utility Patent ☐ Design Patent

is sought on the invention, whose title appears above, the specification of which:

☒ is attached hereto.☐ was filed on _____ as Serial No. _____☐ said application having been amended on _____

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to be material to the patentability of this application in accordance with 37 CFR § 1.56.

I hereby claim foreign priority benefits under 35 U.S.C. § 119(a-d) of any **foreign application(s)** for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of any application on which priority is claimed:

Priority Claimed (If X'd)	Country	Serial Number	Date Filed
<input type="checkbox"/>	_____	_____	_____
<input type="checkbox"/>	_____	_____	_____
<input type="checkbox"/>	_____	_____	_____
<input type="checkbox"/>	_____	_____	_____

I hereby claim the benefit under 35 U.S.C. § 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of 35 U.S.C. § 112, I acknowledge the duty to disclose to the U.S. Patent and Trademark Office all information known to be material to patentability as defined in 37 CFR § 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

Serial Number	Date Filed	Patented/Pending/Abandoned
_____	_____	_____
_____	_____	_____
_____	_____	_____
_____	_____	_____

I hereby claim the benefit under 35 U.S.C. § 119(e) of any United States provisional application(s) listed below:

Serial Number	Date Filed
_____	_____
_____	_____

I hereby appoint the following persons of the firm of **WOODCOCK WASHBURN KURTZ MACKIEWICZ & NORRIS LLP**, One Liberty Place - 46th Floor, Philadelphia, Pennsylvania 19103 as attorney(s) and/or agent(s) to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

<u>Steven J. Rocci</u>	Reg. No. <u>30,489</u>
<u>Steven H. Meyer</u>	Reg. No. <u>37,189</u>

Address all telephone calls and correspondence to:

Steven H. Meyer
**WOODCOCK WASHBURN KURTZ
MACKIEWICZ & NORRIS LLP**
One Liberty Place - 46th Floor
Philadelphia PA 19103
Telephone No.: **(215) 568-3100**
Facsimile No.: **(215) 568-3439**

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Name: Greg Griffith	
Mailing Address:	Signature
City/State of Actual Residence:	Date of Signature: _____
	Citizenship: _____

Name: Charles M. Link, II	
Mailing Address:	Signature
City/State of Actual Residence:	Date of Signature: _____
	Citizenship: _____

Name:	
Mailing Address:	Signature
City/State of Actual Residence:	Date of Signature: _____
	Citizenship: _____

Name:	
Mailing Address:	Signature
City/State of Actual Residence:	Date of Signature: _____
	Citizenship: _____

Name:	
Mailing Address:	Signature
City/State of Actual Residence:	Date of Signature: _____
	Citizenship: _____

Name:	
Mailing Address:	Signature
City/State of Actual Residence:	Date of Signature: _____
	Citizenship: _____

"Bell" 4046/460